

## ACCOR 10W30 VDS 4



220L

4 stroke motor oil

**Fully synthetic**

**Fully synthetic** lubricant especially recommended for the lubrication of **diesel engines for heavy duty vehicles** requiring **EURO 1 to 6** emission standards and equipped with **EGR system** (Exhaust Gas Recirculation) with or without **particulate filters** or with a **system of reduction of Nitrogen Oxides** (Selective Catalyst Reduction technology).

### PERFORMANCE

**ACEA E9/E7 | API CJ4 / CI4+ / CI4**  
**MB 228.31 | MAN 3575**  
**VOLVO VDS-4 | Renault Trucks RLD-3**  
**Cummins CES 20081 | Caterpillar ECF-3, ECF-2 | DEUTZ DQC III-10 LA**

#### «Low-SAPS» oil

Limited content in sulphated ash, sulfur and phosphor  
Longevity of those new post-systems improved.

**Excellent dispersive, antioxidant and anti-corrosion properties**

**Exceptional anti wear and detergent properties**

**Excellent service stability**

#### Technical data

Viscosity at 40°C (cSt): 75  
Viscosity at 100°C (cSt): 11.8  
Viscosity index: 155  
Density at 20°C: 0.852  
Dynamic viscosity at -25°C (cP): 6500

The given data are typical data.