

ECOSYNN 504/507 5W30



5L | 30L | 60L | 220L

4 stroke motor oil

Fully synthetic

High technology fully synthetic oil dedicated to recent Volkswagen motors (**Volkswagen, Audi, Seat, Skoda**) (diesel or petrol) of passenger cars (except models R5 and V10 TDI before 2006). It meets the latest requirements of the Volkswagen group with regards to the drain intervals: **Longlife III service**.

PERFORMANCE

ACEA C3 | VW 504.00 / 507.00
(Compatible VW 501.01/502.00/503.00/503.01/505.00/505.01/506.00/506.01)
BMW LL04 | MB 229.31/229.51 | PORSCHE C30

“Mid-SAPS” oil

Limited proportion of Sulphated Ash, Phosphorus and Sulphur.
Preserve the lifespan of those new post-treatment systems (particulate filters, 3-way catalyst).

Dispersing and detergent properties

Excellent engine protection and cleanliness.

Low volatility

Oil consumption reduction.

High temperature stability

Full protection at very high temperature.

High viscosity index

Perfectly suitable for use all year round.

Caractéristiques

Viscosity at 40°C (cSt): 72
Viscosity at 100°C (cSt): 12.2
Viscosity index: 168
Viscosity at -30°C (cP): 6350
Density at 20°C: 0.850

The given data are typical data.