

ZT3 MULTI 15W40 SHPD



5L | 30L | 60L | 220L

4 stroke motor oil

Mineral

Mineral oil with very high performances, recommended for **fleet vehicles**, equipped with or without **diesel turbo engines**, answering the **EURO 1 to 5** standards and used on prolonged motorway driving, mixed itineraries or deliveries in urban area as well as operating on site.

It is suitable for turbo-charged diesel engines working with both low and heavy load (truck + trailer on motorway).

Recommended for the use of fuel with low sulfur content and for most vehicles using EGR system (Exhaust Gas Recirculation).

PERFORMANCE

**API C14 | ACEA E7 | MAN 3275-1 | VOLVO VDS 3
RENAULT TRUCKS RLD 2 | CATERPILLAR ECF-1a/ECF-2
MB 228.3 | CUMMINS CES 20078/77/76 | MACK E0-M PLUS
MTU DDC Type 2 | DEUTZ DQC III-10 | JASO DH-1**

Excellent detergent, dispersive, antioxidant properties and important thermal stability

Extended drain interval (60000 kms)

Excellent viscosity-temperature behaviour

Optimal engine protection

High Total Base Number

Action against sulfur contained in the fuel

Technical data

Viscosity at 40°C (cSt): 110

Viscosity at 100°C (cSt): 14.8

Viscosity index: 138

Density at 20°C: 0.884

Dynamic viscosity at -20°C (cP):

6400

The given data are typical data.