

## ACCOMATIC DEXRON II



2L | 30L | 60L | 220L

Automatic transmission oil

Mineral

Up-market lubricant for **automatic transmission** of vehicles for which a fluid of type DEXRON is advocated.

This red-coloured fluid, providing better performance than the ATF type A suffix A, can also be used in **raising systems, power-steerings, suspensions, and some mechanical gearboxes.**

### PERFORMANCE

**G.M. DEXRON II-D | ALLISON C4 | CATERPILLAR TO2  
MB 236.1 / 236.6 / 236.7  
DENISON | GM Type A Suffix A (TASA)  
MAN 339 L2 / 339 Z1/V1  
VOITH 55,6335 | VOLVO CE 97340  
ZF TE-ML 05L/21L/09/11A/04D/14A**

#### High viscosity index

Bon fonctionnement à froid / Good cold operation

#### High resistance to oxidation

Chemical stability over time.

#### Protection against rust, deposits, wear and foaming

Prevents clogging of power channels

#### "Extreme pressure" property

Longer service life of gearboxes.

#### Very good friction properties

Prevents skating and jerking when clutching.

#### Technical data

Colour : red

Viscosity at 40°C (cSt) : 40

Viscosity at 100°C (cSt) : 7.7

Viscosity index : 166

Density at 20°C : 0.869

The given data are typical data