

### ACCOGRAISSE EP2



400g | 900g | 5Kg | 25Kg | 50Kg | 180Kg

#### Grease

**High quality lithium grease**, for multiple uses, **insoluble in water** developed for **equipment working under high temperature and heavy loads**. It is suitable for the lubrication of : loaded bearings, ball bearings, gears, articulations, coupling, sliding channels, universal joints, water pumps, civil engineering equipment, ...

#### NLGI 2

##### «Extreme pressure» additives

Wear components in movement reduced.

##### Anticorrosion additive

Protection of all mechanical elements.

##### High thermic stability under heavy loads

##### Technical data

Nature of the soap : lithium

Colour : amber | Appearance : smooth

Penetration [NF T 60-132] (1/10 mm) : 265/295

Corrosion Cu 3 h/100°C [ASTM D 4048] (b) : 1

Limit temperature of use (°C) : -20 to +140

EMCOR Test distilled water [NF T 60-135] : 0

4 weld balls [ASTM D 2596] (Kg) : 250

4 wear balls 1h/40kg [ASTM D 2266] (mm) : 0.55

Oxidation after 100h [ASTM D 942] (psi) : < 6

Wash out [ASTM D 1264] at 80°C (% weight) : < 4

Wheel bearing [ASTM D 1263] at 105°C (g) : 2

Drop point [METTLER method] (°C) : 195

The given data are typical data.

\*Please regularly check that you have the latest up-to-date technical data sheet.